

# Package: alesia (via r-universe)

September 1, 2024

**Title** 'HTML' Minifier Middleware for 'Ambiorix'

**Version** 0.0.1.9000

**Description** 'HTML' minifier middleware for 'Ambiorix'.

**License** GPL (>= 2)

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.1.2

**Imports** V8

**Repository** https://devopifex.r-universe.dev

**RemoteUrl** https://github.com/devOpifex/alesia

**RemoteRef** HEAD

**RemoteSha** 2245eeb2d5bff2b7057a6f5cf519141cba4ba492

## Contents

alesia	1
minify	4

## Index

7

---

alesia

*Alesia*

---

## Description

Alesia

## Usage

```
alesia(
    caseSensitive = FALSE,
    collapseBooleanAttributes = TRUE,
    collapseInlineTagWhitespace = TRUE,
    collapseWhitespace = TRUE,
    conservativeCollapse = TRUE,
    continueOnParseError = TRUE,
    customAttrAssign = list(),
    customAttrSurround = list(),
    decodeEntities = FALSE,
    html5 = TRUE,
    includeAutoGeneratedTags = TRUE,
    keepClosingSlash = FALSE,
    minifyCSS = TRUE,
    minifyJS = TRUE,
    minifyURLs = TRUE,
    preserveLineBreaks = FALSE,
    preventAttributesEscaping = FALSE,
    processConditionalComments = FALSE,
    quoteCharacter = """",
    removeAttributeQuotes = TRUE,
    removeComments = TRUE,
    removeEmptyAttributes = TRUE,
    removeEmptyElements = FALSE,
    removeOptionalTags = FALSE,
    removeRedundantAttributes = FALSE,
    removeScriptTypeAttributes = FALSE,
    removeStyleLinkTypeAttributes = FALSE,
    sortAttributes = FALSE,
    sortClassName = FALSE,
    trimCustomFragments = FALSE,
    useShortDoctype = FALSE
)
```

## Arguments

**caseSensitive** Treat attributes in case sensitive manner (useful for custom HTML tags) | false |  
**collapseBooleanAttributes**  
Omit attribute values from boolean attributes | false |  
**collapseInlineTagWhitespace**  
Don't leave any spaces between display:inline; elements when collapsing. Must be used in conjunction with collapseWhitespace=true | false |  
**collapseWhitespace**  
Collapse white space that contributes to text nodes in a document tree | false |  
**conservativeCollapse**  
Always collapse to 1 space (never remove it entirely). Must be used in conjunction with collapseWhitespace=true | false |

```
continueOnParseError
    Handle parse errors instead of aborting. | false |
customAttrAssign
    Arrays of regex'es that allow to support custom attribute assign expressions (e.g.
    <div flex?="{{mode != cover}}"></div>) | [ ] |
    [ ]: R:%20
customAttrSurround
    Arrays of regex'es that allow to support custom attribute surround expressions
    (e.g. <input {{#if value}}checked="checked"{{/if}}>) | [ ] |
    [ ]: R:%20
decodeEntities Use direct Unicode characters whenever possible | false |
html5 Parse input according to HTML5 specifications | true |
includeAutoGeneratedTags
    Insert tags generated by HTML parser | true |
keepClosingSlash
    Keep the trailing slash on singleton elements | false |
minifyCSS Minify CSS in style elements and style attributes (uses clean-css) | false (could
    be true, Object, Function(text, type)) |
minifyJS Minify JavaScript in script elements and event attributes (uses UglifyJS) | false
    (could be true, Object, Function(text, inline)) |
minifyURLs Minify URLs in various attributes (uses relateurl) | false (could be String, Object,
    Function(text)) |
preserveLineBreaks
    Always collapse to 1 line break (never remove it entirely) when whitespace be-
    tween tags include a line break. Must be used in conjunction with collapse-
    Whitespace=true | false |
preventAttributesEscaping
    Prevents the escaping of the values of attributes | false |
processConditionalComments
    Process contents of conditional comments through minifier | false |
quoteCharacter Type of quote to use for attribute values (' or ") ||
removeAttributeQuotes
    Remove quotes around attributes when possible | false |
removeComments Strip HTML comments | false |
removeEmptyAttributes
    Remove all attributes with whitespace-only values | false (could be true, Func-
    tion(attrName, tag)) |
removeEmptyElements
    Remove all elements with empty contents | false |
removeOptionalTags
    Remove optional tags | false |
removeRedundantAttributes
    Remove attributes when value matches default. | false |
```

```

removeScriptTypeAttributes
    Remove type="text/javascript" from script tags. Other type attribute values are
    left intact | false |
removeStyleLinkTypeAttributes
    Remove type="text/css" from style and link tags. Other type attribute values are
    left intact | false |
sortAttributes  Sort attributes by frequency | false |
sortClassName  Sort style classes by frequency | false |
trimCustomFragments
    Trim white space around ignoreCustomFragments. | false |
useShortDoctype
    Replaces the doctype with the short (HTML5) doctype | false |

```

---

**minify***Minify***Description**

Minify HTML.

**Usage**

```

minify(
  html,
  caseSensitive = FALSE,
  collapseBooleanAttributes = TRUE,
  collapseInlineTagWhitespace = TRUE,
  collapseWhitespace = TRUE,
  conservativeCollapse = TRUE,
  continueOnParseError = TRUE,
  customAttrAssign = list(),
  customAttrSurround = list(),
  decodeEntities = FALSE,
  html5 = TRUE,
  includeAutoGeneratedTags = TRUE,
  keepClosingSlash = FALSE,
  minifyCSS = TRUE,
  minifyJS = TRUE,
  minifyURLs = TRUE,
  preserveLineBreaks = FALSE,
  preventAttributesEscaping = FALSE,
  processConditionalComments = FALSE,
  quoteCharacter = "'",
  removeAttributeQuotes = TRUE,
  removeComments = TRUE,
  removeEmptyAttributes = TRUE,

```

```
removeEmptyElements = FALSE,  
removeOptionalTags = FALSE,  
removeRedundantAttributes = FALSE,  
removeScriptTypeAttributes = FALSE,  
removeStyleLinkTypeAttributes = FALSE,  
sortAttributes = FALSE,  
sortClassName = FALSE,  
trimCustomFragments = FALSE,  
useShortDoctype = FALSE  
)
```

## Arguments

html	HTML string to minify.
caseSensitive	Treat attributes in case sensitive manner (useful for custom HTML tags)   false   collapseBooleanAttributes
	Omit attribute values from boolean attributes   false
collapseInlineTagWhitespace	Don't leave any spaces between display:inline; elements when collapsing. Must be used in conjunction with collapseWhitespace=true   false
collapseWhitespace	Collapse white space that contributes to text nodes in a document tree   false
conservativeCollapse	Always collapse to 1 space (never remove it entirely). Must be used in conjunction with collapseWhitespace=true   false
continueOnParseError	Handle parse errors instead of aborting.   false
customAttrAssign	Arrays of regex'es that allow to support custom attribute assign expressions (e.g. <div flex?="{{mode != cover}}></div>)   [ ]   [ ]: R:%20
customAttrSurround	Arrays of regex'es that allow to support custom attribute surround expressions (e.g. <input {{#if value}}checked="checked"{{/if}}>)   [ ]   [ ]: R:%20
decodeEntities	Use direct Unicode characters whenever possible   false
html5	Parse input according to HTML5 specifications   true
includeAutoGeneratedTags	Insert tags generated by HTML parser   true
keepClosingSlash	Keep the trailing slash on singleton elements   false
minifyCSS	Minify CSS in style elements and style attributes (uses <a href="#">clean-css</a> )   false (could be true, Object, Function(text, type))
minifyJS	Minify JavaScript in script elements and event attributes (uses <a href="#">UglifyJS</a> )   false (could be true, Object, Function(text, inline))

minifyURLs Minify URLs in various attributes (uses `relateurl`) | false (could be String, Object, Function(text)) |

preserveLineBreaks Always collapse to 1 line break (never remove it entirely) when whitespace between tags include a line break. Must be used in conjunction with collapseWhitespace=true | false |

preventAttributesEscaping Prevents the escaping of the values of attributes | false |

processConditionalComments Process contents of conditional comments through minifier | false |

quoteCharacter Type of quote to use for attribute values (' or ") | |

removeAttributeQuotes Remove quotes around attributes when possible | false |

removeComments Strip HTML comments | false |

removeEmptyAttributes Remove all attributes with whitespace-only values | false (could be true, Function(attrName, tag)) |

removeEmptyElements Remove all elements with empty contents | false |

removeOptionalTags Remove optional tags | false |

removeRedundantAttributes Remove attributes when value matches default. | false |

removeScriptTypeAttributes Remove type="text/javascript" from script tags. Other type attribute values are left intact | false |

removeStyleLinkTypeAttributes Remove type="text/css" from style and link tags. Other type attribute values are left intact | false |

sortAttributes Sort attributes by frequency | false |

sortClassName Sort style classes by frequency | false |

trimCustomFragments Trim white space around ignoreCustomFragments. | false |

useShortDoctype Replaces the doctype with the short (HTML5) doctype | false |

# Index

alesia, 1

minify, 4